

## ATTACHMENT 2

### Asbestos Personal Sampling Results - Chlorine Cell Line

**Axiall, a Westlake Company**  
**Plaquemine, LA**

Sample ID	Date	Employee Task	Time (min)	PCM Results (f/cc)
				Analytics
PLQ-100316-003	10/03/2016	Cell Line Operator	484	<0.005
PLQ-100316-004	10/03/2016	Cell Line Operator	484	<0.005
PLQ-100416-001	10/04/2016	Cell Line Operator	470	<0.005
PLQ-100416-002	10/04/2016	Cell Line Operator	459	<0.005
PLQ-100516-003	10/05/2016	Cell Line Operator	473	<0.005
PLQ-100516-004	10/05/2016	Cell Line Operator	473	<0.005
PLQ-100616-001	10/06/2016	Cell Line Operator	477	<0.005
PLQ-100616-002	10/06/2016	Cell Line Operator	476	<0.005

f/cc : fibers per cubic centimeter of air

OSHA-PEL (Permissible Exposure Limit) for asbestos is 0.1 f/cc for an 8 hour Time Weighted Average (8-hr TWA).

OSHA-STEL (Short Term Excursion Limit) for asbestos is 1.0 f/cc for a 30-minute Time Weighted Average (30-min TWA).

Analytical Method: NIOSH 7400 - Asbestos and Other Fibers by Phase Contrast Microscopy